

DC/DC down converter

The invention relates to a DC/DC down converter which comprises a synchronous rectifier, a switching element at its input side and an inductance at its output side.

DC/DC down converters of this kind (Buck converters for DC/DC conversion) are intended, for example, for power supply of digital switching circuits, notably processors of PCs, where a voltage conversion of typically from 5 ... 12 volts to 1.5 ... 3.3 volts takes place. In contemporary digital switching circuits, the DC supply voltage to be generated even goes to values below 1.5 volts; it is then additionally necessary to adapt the DC/DC down converter to increasingly faster load fluctuations. Therefore, the down converter has to operate with correspondingly high switching frequencies of the switching elements used (synchronous rectifier and switching element at the input side customarily being field effect transistors); however, increasing switching frequencies give rise to increasing losses. Therefore, the switching frequency cannot be increased at will. In order to permit faster load fluctuations nevertheless, the output filter capacitances of the relevant down converter are increased; however, such an increase leads to higher costs.

As the switching frequencies become higher, the ratio of the switching losses to the losses produced in the conductive state of the switching elements become larger and larger. On the one hand, the losses which occur due to the alternating turning on and off of the synchronous rectifier and the switching element at the input side become larger and larger because of the simultaneous presence of currents and voltages on the switching elements during the transition between turn-on phases and turn-off phases. On the other hand, as the switching frequencies increase, losses which are due to reverse flow or reverse recovery of the body diode of the synchronous rectifier, which is customarily implemented as a field effect transistor, start to form a substantial part of the overall losses. Moreover, losses are also caused by the hard switching of the parasitic capacitances (notably of the two switching elements).

It is an object of the present invention to provide a DC/DC down converter which permits fast load fluctuations, which is as economical as possible and in which the operating losses are as low as possible.

This object is achieved by means of an auxiliary circuit which includes an auxiliary switching element, an auxiliary rectifier and an auxiliary inductance, the auxiliary circuit being coupled to the connection between the synchronous rectifier, the switching element at the input side and the inductance at the output side.

5 Using an auxiliary circuit of this kind, practically voltage-free or so-called zero voltage switching can be achieved for the switching element at the input side as well as for the synchronous rectifier while losses due to reverse recovery of the body diode of the synchronous rectifier can be avoided at the same time.

Claim 2 elucidates the arrangement of the elements of the auxiliary circuit.

10 The characteristics of claim 3 define the time slot in which the auxiliary switching element is in the turned-on state, so that losses due to reverse recovery of the body diode of the synchronous rectifier are avoided.

Claim 4 describes the turn-on instant of the switching element at the input side, thus enabling zero-voltage switching. As an alternative to claim 4, claim 5 discloses a
15 voltage measurement so that it can be ensured that the switching element at the input side is turned on when the voltage is sufficiently low.

Claim 6 discloses a suitable turn-off instant for the synchronous rectifier.

An embodiment of the invention will be described in detail hereinafter with reference to the drawings. Therein:

20 Fig. 1 shows a DC/DC down converter in accordance with the invention, and Figs. 2A to 2I show the variations of voltages and currents as a function of time during operation of the DC/DC down converter shown in Fig. 1.

The DC/DC down converter shown in Fig. 1 comprises a switching element C at the input side, a synchronous rectifier S and an inductance L at the output side. The
25 switching element C at the input side and the synchronous rectifier S are both implemented as field effect transistors. The switching element C includes a body diode D_C which is connected between its drain terminal and its source terminal and also includes a capacitance C_C which is connected parallel thereto and which may also include, if necessary, an external capacitance in addition to the parasitic capacitance of the switching element C. The
30 synchronous rectifier S includes a body diode D_S which is connected between its drain terminal and its source terminal and also a capacitance C_S which is connected parallel thereto and which may also include, if necessary, an external capacitance in addition to the parasitic capacitance of the synchronous rectifier S. The switching element C, the synchronous rectifier S and the inductance L are connected in a star configuration and are connected to

one another at a node P1. An input voltage U_{in} is applied to the input of the DC/DC down converter. An output voltage U_{out} can be derived from the output of the DC/DC down converter, which output voltage drops off across an output capacitance C_{out} which may comprise one or more capacitors. The output capacitance C_{out} is connected in series with the inductance L .

There is also provided an auxiliary circuit H which consists of an auxiliary switching element A, an auxiliary rectifier D_{aux} which is constructed as a diode, and a small auxiliary inductance L_{aux} which is constructed as a coil, said elements being connected in a star configuration with a node P2. The auxiliary switching element A is implemented as a field effect transistor with a body diode D_A which is connected between the drain and source terminals and a capacitance C_A which is connected parallel thereto and which constitutes the parasitic capacitance of the auxiliary switching element A. The auxiliary circuit H is connected to the node P1 and is situated between the input of the DC/DC down converter, carrying the voltage U_{in} , and the synchronous rectifier S. The drain terminal of the auxiliary switching element A is then connected to the input terminal carrying the positive potential of the input voltage U_{in} . The other input terminal is connected to a reference potential GND which is also connected to the anode of the diode D_{aux} , the source terminal of the synchronous rectifier S and a terminal of the output capacitance C_{out} . The cathode of the diode D_{aux} is connected to the source terminal of the auxiliary switching element A and to a terminal of the auxiliary inductance L_{aux} , the other terminal of the auxiliary inductance L_{aux} being connected to the point P1.

Figs. 2A to 2I show various variations of voltages and currents so as to illustrate the operation of the circuit arrangement in conformity with Fig. 1.

Fig. 2A: potential GA on the control terminal (gate terminal) of the auxiliary switching element A;

Fig. 2B: potential GC on the control terminal (gate terminal) of the switching element C at the input side;

Fig. 2C: potential GS on the control terminal (gate terminal) of the synchronous rectifier S;

Fig. 2D: current IAM through the auxiliary switching element A in the direction of the node P2;

Fig. 2E: current IC through the switching element C at the input side in the direction of the node P1;

Fig. 2F: current I_S through the synchronous rectifier S in the direction from the node $P1$ to the reference potential GND ;

Fig. 2G: current I_{AD} from the reference potential GND through the auxiliary rectifier D_{aux} in the direction of the node $P2$;

5 Fig. 2H: voltage U_C on the switching element C on the input side in the direction from the input voltage U_{in} to the node $P1$, and

Fig. 2I: voltage U_S on the synchronous rectifier in the direction from the node $P1$ to the reference potential GND .

10 Interval $t_0 \leq t < t_1$:

At the instant t_0 the auxiliary switching element A is turned on. At this instant the switching element C at the input side is turned off and the synchronous rectifier S is turned on. As a result of the turning on of the auxiliary switching element A , the current I_{AM} increases steeply from the value zero, the steepness of the rise being dependent on the value
 15 of the inductance L_{aux} which is small in comparison with the inductance L . The auxiliary switching element A is thus turned on with so-called zero current switching, that is, at a current I_{AM} equal to zero. The current I_C through the switching element C at the input side equals zero. On the current I_S , increasing with a flat rise until the instant t_0 (corresponding to a decrease of the absolute value of the current I_S which is negative until this instant), there is
 20 superposed the current I_{AM} , so that I_S increases with a correspondingly steeper rise and enters the positive range of values between the instant t_0 and a subsequent instant t_1 , so that as from that instant the synchronous rectifier can be turned off (with positive values of I_S) without reverse recovery (generating losses) of the body diode D_S , because the body diode has never conducted current in the case of customarily used MOSFETs. The rectifier D_{aux} is
 25 turned off and I_{AD} is zero for as long as the auxiliary switching element A is turned on. The voltage U_C is equal to the input voltage U_{in} . The voltage U_S equals zero.

Interval $t_1 \leq t < t_2$:

The auxiliary switching element A remains turned on and the switching
 30 element C now remains turned off; however, the turning on of the switching element C is permissible in principle as from the instant t_1 (denoted by the double arrow on the ascending edge of the control potential G_C in Fig. 2B), since as from this instant the current I_C is negative and hence, while the body diode D_C is turned on, the switching element C can be turned on with zero voltage switching which minimizes switching losses. The synchronous

rectifier S is turned off at the instant t_1 . The current I_{AM} remains essentially constant between the instants t_1 and t_2 . The current I_C assumes a negative value and remains substantially constant until the instant t_2 . The current I_S has now assumed the value zero. The current I_{AD} is still zero. The voltage U_C returns to zero, the steepness of the drop of U_C being dependent on the value of the capacitances C_C and C_S which is switched during the drop. The dashed descending line in Fig. 2A represents a case where the voltage has dropped to zero in a delayed fashion only at the instant t_1' . Preferably, the voltage U_C is measured and compared with a threshold value; when the voltage U_C has decreased sufficiently, the switching element C can be turned on, only correspondingly small losses then being induced in the switching element C. The voltage U_S on the switching element S increases to the value of the input voltage U_{in} as from the instant t_1 , the steepness of the rise again being dependent on the value of the capacitances C_C and C_S switched during the rise of the voltage U_S . The dashed ascending line in Fig. 2I represents a case where the voltage U_S has increased to the value of U_{in} in a delayed fashion only at the instant t_1' . The switching element S is turned off at the instant t_1 with zero voltage switching, that is, U_S is equal to zero at the instant t_1 .

Interval $t_2 \leq t < t_3$:

At the instant t_2 the auxiliary switching element A is turned off, so that the current I_{AM} becomes zero. The inductance L_{aux} is discharged via the rectifier D_{aux} wherethrough a decreasing current I_{AD} flows at this time. The absolute value of the current I_C decreases from the (negative) value at the instant t_2 until it reaches the value zero at the instant t_3 . The switching element C is turned on at the instant t_2' ; this takes place while the body diode D_C is turned on or while a voltage U_C is detected whose absolute value is sufficiently low, that is, with zero voltage switching (see also the above description in relation to the instant $t_1 \leq t < t_2$ for the interval in which the switching element C can be turned on).

Interval $t_3 \leq t < t_4$:

The auxiliary switching element A and the synchronous rectifier S remain turned off and the switching element C remains turned on. The current I_{AD} through the auxiliary rectifier D_{aux} continues to decrease with the same steepness as in the time interval $t_2 \leq t < t_3$. At the instant t_4 the current I_{AD} has decreased to zero. The current I_C continues to increase constantly with the same steepness as in the time interval $t_2 \leq t < t_3$ with the value zero at the instant t_3 .

Time interval $t_4 \leq t < t_5$:

At the instant t_4 the auxiliary inductance L_{aux} has been completely discharged and hence the current I_{AD} has reached the value zero and remains zero. As a result, while the switching element C is still turned on the current I_C increases less strongly than in the time interval $t_3 \leq t < t_4$.

Time interval $t_5 \leq t < t_6$:

At the instant t_5 the switching element C is turned off and the synchronous rectifier S is turned on. Consequently, the current I_C decreases to zero. At the instant t_5 the current I_S jumps from zero to a negative value as from which the current I_S increases until the instant t_6 while its absolute value decreases accordingly (in the case of small loads or a zero load I_S increases to positive values until the instant t_6). The voltage U_C increases to the value of U_{in} at the instant t_5 . Because the associated switching of the capacitances C_C and C_S cannot be arbitrarily fast, and the corresponding rise of the voltage U_C and decrease of the voltage U_S do not take place with an infinite steepness, a small idle time (not recognizable in the Figs. 2A to 2I) is provided for turning on the switching element S ; this means that the switching element S is turned on only a brief period of time after the turning off of the switching element C , thus ensuring that the turning on of the switching element S takes place with zero voltage switching.

The operations described for the interval from t_0 to t_6 are repeated as from the instant t_6 .

The events taking place between the instants t_0 and t_4 are shown so as to be stretched in time in the Figs. 2A to 2I for a better illustration of the invention. In reality the ratio of the interval from t_0 to t_4 to the interval t_0 to t_6 is significantly smaller than shown in the Figs. 2A to 2I.